



Australian Government

**Department of Infrastructure, Transport,
Regional Development, Communications and the Arts**

**Department of Infrastructure, Transport, Regional Development, Communications and the Arts
Vehicle Safety Operations Branch**

Road-Friendly Suspension Certificate Number (RFCN): RF2002

Issue Date: 10th February 2022

The Assistant Secretary, Vehicle Safety Standards Branch has assessed the information in Schedule 3 for the suspension described in Road Friendly Certificate Schedule 2, which the Supplier identified in Schedule 1 has submitted as complying with the road-friendliness requirements as specified in National Road Transport Commission (NRTC) publication 'Road-Friendly Suspension—Performance and Component Requirements, and Acceptable Test methods'. This information will be acceptable for use as evidence of compliance with the requirements specified in the NRTC publication provided the suspension is installed according to the Supplier's nominated installation instructions identified in Schedule 3.

The issue of this Certificate is subject to the following conditions:

1. The Supplier shall not quote the Road-Friendly Certificate Number in respect of a suspension which is not the suspension certified in the Road-Friendly Suspension certificate with that number.
2. Without the prior approval of the Assistant Secretary, Vehicle Safety Standards Branch, the Supplier shall not quote Road-Friendly Certificate Number in respect of a suspension, that is in any way different from the suspension described in the final form of the application for this Suspension Certificate Number. The application includes reports and other information relating to the application.
3. The Supplier shall by detailed quality control and test ensure continuing compliance with the requirements.
4. The Supplier shall maintain records of detailed quality control and test documentation.
5. The Supplier shall supply upon request, to Assistant Secretary, Vehicle Safety Standards Branch any additional information requested for the purpose of demonstrating compliance.
6. The Supplier shall not quote the Road-Friendly Certificate Number in respect of a suspension on or after the Expiry date specified in the certificate.
7. The Supplier shall indicate by an appropriate method (decal, label or plate) the Road-Friendly Suspension Certificate Number (RFCN) on the suspension system.
8. On cessation of marketing the specified suspension in Australia, the Supplier shall notify Assistant Secretary, Vehicle Safety Standards Branch of the date of manufacture of the last specified suspension supplied to the market in Australia.
9. If the requirements for road-friendliness are changed by the National Road Transport Commission, a new approval may be required.

Certificate No: **RF2002**
 Issue Date: **2 September 2020**
 Expiry Date: **Life of Mode**

Schedule 1

Supplier Name: Saf-Holland (Aust) Pty Ltd
Supplier Address: 115–143 High Street, Melton VIC 3337

Supplier ID: L1710

Schedule 2

Make: SAF-HOLLAND
Model: AIR

Schedule 3

	Variant 1	Variant 2	Variant 3	Variant 4	Variant 5
Variant name:	H041C3	H041A3	H042C3	H042A3	U514A3
Number of Axles	3	3	3	3	3
Overslung/Underslung	Underslung	Underslung	Overslung	Overslung	Underslung
Maximum Axle spread (m)	3.200	3.200	3.200	3.200	3.200
Dampers Part Numbers	902398	902022110-299	902398	902022110-299	902022110-299
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	370	370	370	370	300
Reference Drawings No of Suspension (parts list & assembly details)	40100, 40055	40100, 40055	40101, 40055	40101, 40055	40103, 40055

	Variant 6	Variant 7	Variant 8	Variant 9	Variant 10
Variant name:	U524A3	U534A3	E510A3	E520A3	E530A3
Number of Axles	3	3	3	3	3
Overslung/Underslung	Overslung	Overslung	Underslung	Overslung	Overslung
Maximum Axle spread (m)	3.200	3.200	3.200	3.200	3.200
Dampers Part Numbers	902022110-299	902022110-299	902022110-299	902022110-299	902022110-299
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	300	300	300	300	300
Reference Drawings No of Suspension (parts list & assembly details)	40104, 40055	40105, 40055	40106, 40055	40107, 40055	40108, 40055

	Variant 11	Variant 12	Variant 13	Variant 14	Variant 15
Variant name:	H041C2	H041B2	H042C2	H042B2	U514A2
Number of Axles	2	2	2	2	2
Overslung/Underslung	Underslung	Underslung	Overslung	Overslung	Underslung
Maximum Axle spread (m)	2.000	2.000	2.000	2.000	2.000
Dampers Part Numbers	902398	902194	902398	902194	902022110-299
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	370	370	370	370	300
Reference Drawings No of Suspension (parts list & assembly details)	40100, 40055	40100, 40055	40101, 40055	40101, 40055	40103, 40055

	Variant 16	Variant 17	Variant 18	Variant 19	Variant 20
Variant name:	U524A2	U534A2	E510A2	E520A2	E530A2
Number of Axles	2	2	2	2	2
Overslung/Underslung	Overslung	Overslung	Underslung	Overslung	Overslung
Maximum Axle spread (m)	2.000	2.000	2.000	2.000	2.000
Dampers Part Numbers	902022110-299	902022110-299	902022110-299	902022110-299	902022110-299
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	300	300	300	300	300
Reference Drawings No of Suspension (parts list & assembly details)	40104, 40055	40105, 40055	40106, 40055	40107, 40055	40108, 40055

	Variant 21	Variant 22	Variant 23	Variant 24	Variant 25
Variant name:	AD126-11	AD123-10	RL228-15-02	AD246-10	AD252-11
Number of Axles	1	1	2	2	2
Overslung/Underslung	Underslung	Underslung	Overslung	Underslung	Underslung
Maximum Axle spread (m)	1.000	1.000	2.000	2.000	2.000
Dampers Part Numbers	3501002	3501001	4501001	3501001	3501002
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	371	327	368	367	371
Reference Drawings No of Suspension (parts list & assembly details)	40200	32000290	10000338	32000290	40200

	Variant 26	Variant 27	Variant 28	Variant 29	Variant 30
Variant name:	RL228-15-03	AD369-10	AD378-11	AD246-8.15	AD252-10
Number of Axles	3	3	3	2	2
Overslung/Underslung	Overslung	Underslung	Underslung	Underslung	Underslung
Maximum Axle spread (m)	3.200	3.200	3.200	2.000	2.000
Dampers Part Numbers	4501001	3501001	3501002	3501001	3501002
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	368	327	371	327	371
Reference Drawings No of Suspension (parts list & assembly details)	10000338	32000290	40200	32000293	32000264

	Variant 31	Variant 32	Variant 33	Variant 34	Variant 35
Variant name:	RL250-15-03	AD260-10	AD390-10	SAF01 E SERIES	SAF INTRA IU 03-300
Number of Axles	3	2	3	3	3
Overslung/Underslung	O/SLUNG	U/SLUNG	U/SLUNG	Underslung	U/SLUNG
Maximum Axle spread (m)	3.200	2.000	3.200	3.200	3.2000
Dampers Part Numbers	KONI 881547	3501001	3501001	23553-01	2 376 5070 00 2 376 5071 00 2 376 5072 00 2 376 0084 00 2 376 0085 00 2 376 0086 00
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	380	370	370	350	300
Reference Drawings No of Suspension (parts list & assembly details)	10000431	40390	4390	EU 416 E, EU 416, EM 411 H, EM 411 EH, EO 414 H, EO 414 EH, AR 413	182 83 03 7 69 0 182 83 10 7 69 0 182 83 06 7 69 0 182 83 12 7 69 0 182 83 03 7 69 13 182 83 30 7 69 10 182 83 85 7 69 13 P00 21 50 6 20 23

	Variant 36	Variant 37	Variant 38	Variant 39	Variant 40	Variant 41
Variant name:	Combined with 52	SAF MODUL US 3503	See variant 53	SAF INTRA IU 02-300	See variant 51	SAF MODUL US 3502
Number of Axles	3			2		2
Overslung/Underslung		U/SLUNG		U/SLUNG		U/SLUNG
Maximum Axle spread (m)		3.2000		2.000		2.000
Dampers Part Numbers		2 376 5027 00 2 376 5030 00 2 376 5031 00 2 376 0027 00 2 376 0031 00 2 376 0032 00 2 376 5032 00		2 376 5070 00 2 376 5071 00 2 376 5072 00 2 376 0084 00 2 376 0085 00 2 376 0086 00		2 376 5027 00 2 376 5030 00 2 376 5031 00 2 376 0027 00 2 376 0031 00 2 376 0032 00 2 376 5032 00
Smallest Tyre Size Designation		8.25R15		8.25R15		8.25R15
Highest tyre pressure (Kpa)		825		825		825
Airbag Diameter (mm)		350		300		350
Reference Drawings No of Suspension (parts list & assembly details)		183 90 95 2 69 0 283 90 03 2 69 0 283 90 04 2 69 0 P00221092023 683836776910		182 83 03 7 69 0 182 83 10 7 69 0 182 83 06 7 69 0 182 83 12 7 69 0 182 83 03 7 69 13 182 83 30 7 69 10 182 83 85 7 69 13 P00 21 50 6 20 23		183 90 95 2 69 0 283 90 03 2 69 0 283 90 04 2 69 0 P00221092023 683836776910

	Variant 42	Variant 43	Variant 44	Variant 45	Variant 46
Variant name:	See variant 54	SAF INTRA IU 01-300	SAF MODUL US 3001	SAF MODUL US 3501	See variant 55
Number of Axles		1	1	1	
Overslung/Underslung		U/SLUNG	U/SLUNG	U/SLUNG	
Maximum Axle spread (m)		0.000	0.000	0.000	
Dampers Part Numbers		2 376 5070 00 2 376 5071 00 2 376 5072 00 2 376 0084 00 2 376 0085 00 2 376 0086 00	2 376 5027 00 2 376 5030 00 2 376 5031 00 2 376 0027 00 2 376 0031 00 2 376 0032 00	2 376 5027 00 2 376 5030 00 2 376 5031 00 2 376 0027 00 2 376 0031 00 2 376 0032 00 2 376 5032 00	
Smallest Tyre Size Designation		8.25R15	8.25R15	8.25R15	
Highest tyre pressure (Kpa)		825	825	825	
Airbag Diameter (mm)		300	300	350	

	Variant 42	Variant 43	Variant 44	Variant 45	Variant 46
Reference Drawings No of Suspension (parts list & assembly details)	182 83 03 7 69 0	182 83 10 7 69 0	183 90 95 2 69 0	283 90 04 2 69 0	
	182 83 06 7 69 0	182 83 12 7 69 0	283 90 03 2 69 0	P00221092023	
	182 83 03 7 69 13	P000150507	183 90 94 2 69 0	683836776910	
	182 83 30 7 69 10	P00129082023			
	182 83 85 7 69 13	683836776910			
	P00 21 50 6 20 23	C18312046690			
		C18312016690			

	Variant 47	Variant 48	Variant 49	Variant 50	Variant 51
Variant name:	SAF INTRA IO 01-300	SAF INTRA IO 02-300	SAF INTRA IO 03-300	See variant 35	SAF MODUL US 3002
Number of Axles	1	2	3		2
Overslung/Underslung	O/SLUNG	O/SLUNG	O/SLUNG		U/SLUNG
Maximum Axle spread (m)	0.000	2.000	3.200		2.000
Dampers Part Numbers	2 376 5071 00 2 376 5072 00 2 376 0085 00 2 376 0086 00 2 376 0089 00	2 376 5071 00 2 376 5072 00 2 376 0085 00 2 376 0086 00	2 376 5071 00 2 376 5072 00 2 376 0085 00 2 376 0086 00		2 376 5027 00 2 376 5030 00 2 376 5031 00 2 376 0027 00 2 376 0031 00 2 376 0032 00
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15		8.25R15
Highest tyre pressure (Kpa)	825	825	825		825
Airbag Diameter (mm)	300	300	300		300
Reference Drawings No of Suspension (parts list & assembly details)	182 83 17 7 69 0 182 83 16 7 69 0 182 83 18 7 69 0 182 83 20 7 69 0 282 83 24 7 69 13 182 83 90 7 69 13 182 83 74 7 69 13 182 83 83 7 69 13 182 83 20 7 69 13 P00 10 70 3 20 23 182 90 18 7 69 21	182 83 17 7 69 0 182 83 16 7 69 0 182 83 18 7 69 0 182 83 20 7 69 0 282 83 24 7 69 13 182 83 90 7 69 13 182 83 74 7 69 13 182 83 83 7 69 13 182 83 20 7 69 13 P00 10 70 3 20 23 182 90 18 7 69 21	182 83 17 7 69 0 182 83 16 7 69 0 182 83 18 7 69 0 182 83 20 7 69 0 282 83 24 7 69 13 182 83 90 7 69 13 182 83 74 7 69 13 182 83 83 7 69 13 182 83 20 7 69 13 P00 10 70 3 20 23 182 90 18 7 69 21		183 90 95 2 69 0 283 90 03 2 69 0 183 12 01 6 69 0 183 90 94 2 69 0 P000150507 P00129082023 683836776910 C18312046690 C18312016690

	Variant 52	Variant 53	Variant 54	Variant 55	Variant 56
Variant name:	SAF MODUL US 3003	SAF MODUL OS 3503	SAF MODUL OS 3502	SAF MODUL OS 3501	See variant 51
Number of Axles	3	3	2	1	
Overslung/Underslung	U/SLUNG	O/Slung	O/Slung	O/Slung	
Maximum Axle spread (m)	3.2	3.2	2.000	0.000	
Dampers Part Numbers	2 376 5027 00 2 376 5030 00 2 376 5031 00 2 376 0027 00 2 376 0031 00 2 376 0032 00	2 376 5026 00 2 376 0032 00 2 376 0031 00 2 376 0026 00	2 376 5026 00 2 376 0032 00 2 376 0031 00 2 376 0026 00	2 376 5026 00 2 376 0032 00 2 376 0031 00 2 376 0026 00	
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	
Highest tyre pressure (Kpa)	825	825	825	825	
Airbag Diameter (mm)	300	350	350	350	
Reference Drawings No of Suspension (parts list & assembly details)	183 90 95 2 39 0 283 90 03 2 69 0 183 12 01 6 69 0 183 90 94 2 69 0 P000150507 P00129082023 683836776910 C18312046690 C18312016690	283 90 05 2 69 0, 283 90 06 2 69 0, 283 90 07 2 69 0, 183 90 97 2 69 0, C183 12 03 6 69 0-350, C183 12 02 6 69 0-350, C183 12 05 6 69 0-350 189 83 35 7 69 10 P00415062023 189 83 13 7 69 10 183 83 52 7 66 0 189 83 16 7 69 10 P00114072023	283 90 05 2 69 0, 283 90 06 2 69 0, 283 90 07 2 69 0, 183 90 97 2 69 0, C183 12 03 6 69 0-350, C183 12 02 6 69 0-350, C183 12 05 6 69 0-350 189 83 35 7 69 10 P00415062023 189 83 13 7 69 10 183 83 52 7 66 0 189 83 16 7 69 10 P00114072023	283 90 05 2 69 0, 283 90 06 2 69 0, 283 90 07 2 69 0, 183 90 97 2 69 0, C183 12 03 6 69 0-350, C183 12 02 6 69 0-350, C183 12 05 6 69 0-350 189 83 35 7 69 10 P00415062023 189 83 13 7 69 10 183 83 52 7 66 0 189 83 16 7 69 10 P00114072023	

	Variant 57	Variant 58	Variant 59	Variant 60	Variant 61
Variant name:	SAF MODUL OS 3002	See variant 52	SAF MODUL OS 3003	ADZ246	ADZ252
Number of Axles	2		3	2	2
Overslung/Underslung	O/Slung		O/Slung	Underslung	Underslung
Maximum Axle spread (m)	3.200		2.000	1.378	1.378
Dampers Part Numbers	2376502600 2 376 0031 00 2 376 0026 00 2 376 0032 00		2376502600 2 376 0031 00 2 376 0026 00 2 376 0032 00	90045605	90045605
Smallest Tyre Size Designation	8.25R15		8.25R15	255/70R 22.5	255/70R 22.5
Highest tyre pressure (Kpa)	825		825	825	825
Airbag Diameter (mm)	300		300	320	348

	Variant 57	Variant 58	Variant 59	Variant 60	Variant 61	
Reference Drawings No of Suspension (parts list & assembly details)	C183 12 02 6 69 0, C183 12 03 6 69 0, C183 12 05 6 69 0 P00127092022 283 90 05 2 69 0 P00114072023 683837576910 683837776910 183 90 97 2 69 0 683837676910 P30000074401		C183 12 02 6 69 0, C183 12 03 6 69 0, C183 12 05 6 69 0 P00127092022 283 90 05 2 69 0 P00114072023 683837576910 683837776910 183 90 97 2 69 0 683837676910 P30000074401		PLM-02039 90557395	32000630 90557392

	Variant 62	Variant 63	Variant 64	Variant 65	Variant 66
Variant name:	See variant 82	See variant 85	See variant 45	See variant 55	See variant 41
Number of Axles					
Overslung/Underslung					
Maximum Axle spread (m)					
Dampers Part Numbers					
Smallest Tyre Size Designation					
Highest tyre pressure (Kpa)					
Airbag Diameter (mm)					
Reference Drawings No of Suspension (parts list & assembly details)					

	Variant 67	Variant 68	Variant 69	Variant 70	Variant 71
Variant name:	See variant 54	See variant 37	See variant 53	ADZ-126	ADZ-252
Number of Axles				1	2
Overslung/Underslung				U/Slung	U/Slung
Maximum Axle spread (m)				1.000	2.000
Dampers Part Numbers				90045830	90045830
Smallest Tyre Size Designation				8.25R15	8.25R15
Highest tyre pressure (Kpa)				825	825
Airbag Diameter (mm)				348	348
Reference Drawings No of Suspension (parts list & assembly details)				32000598	32000777

	Variant 72	Variant 73	Variant 74	Variant 75	Variant 76
Variant name:	ADZ-378	SAF INTRA IU 04-300	SAF INTRA IO 04-300	SAF INTRA IU 01-350	SAF INTRA IU 02-350
Number of Axles	2	4	4	1	2
Overslung/Underslung	U/Slung	U/SLUNG	O/SLUNG	U/SLUNG	U/SLUNG
Maximum Axle spread (m)	3.200	4.900	4.900	1.000	2.000
Dampers Part Numbers	90045830	2 376 0084 00 2 376 0085 00 2 376 0086 00	2 376 0085 00 2 376 0086 00 2 376 0089 00	2 376 0084 00 2 376 0085 00 2 376 0086 00	2 376 0084 00 2 376 0085 00 2 376 0086 00
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	348	300	300	350	350
Reference Drawings No of Suspension (parts list & assembly details)	32000734	182 83 03 7 69 13 182 83 30 7 69 10 182 83 85 7 69 13 P00 21 50 6 20 23	282 83 24 7 69 13 182 83 90 7 69 13 182 83 74 7 69 13 182 83 83 7 69 13 182 83 20 7 69 13 P00 10 70 3 20 23 182 90 18 7 69 21	182 83 92 7 69 13 282 83 06 7 69 13 P00 11 00 3 20 23 P00 11 00 7 20 23	182 83 92 7 69 13 282 83 06 7 69 13 P00 11 00 3 20 23 P00 11 00 7 20 23

	Variant 77	Variant 78	Variant 79	Variant 80	Variant 81
Variant name:	SAF INTRA IU 03-350	SAF INTRA IU 04-350	SAF INTRA IO 01-350	SAF INTRA IO 02-350	SAF INTRA IO 03-350
Number of Axles	3	4	1	2	3
Overslung/Underslung	U/SLUNG	U/SLUNG	O/SLUNG	O/SLUNG	O/SLUNG
Maximum Axle spread (m)	3.200	4.900	1.000	2.000	3.200
Dampers Part Numbers	2 376 0084 00 2 376 0085 00 2 376 0086 00	2 376 0084 00 2 376 0085 00 2 376 0086 00	2 376 0085 00 2 376 0086 00 2 376 0089 00	2 376 0085 00 2 376 0086 00 2 376 0089 00	2 376 0085 00 2 376 0086 00 2 376 0089 00
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	350	350	350	350	350
Reference Drawings No of Suspension (parts list & assembly details)	182 83 92 7 69 13 282 83 06 7 69 13 P00 11 00 3 20 23 P00 11 00 7 20 23	182 83 92 7 69 13 282 83 06 7 69 13 P00 11 00 3 20 23 P00 11 00 7 20 23	182 90 09 7 69 21 282 83 07 7 69 13 IAT 01 20 2 01 5 182 83 93 7 69 13 P00 11 20 1 20 23 282 83 08 7 66 13 182 90 18 7 69 21	182 90 09 7 69 21 282 83 07 7 69 13 IAT 01 20 2 01 5 182 83 93 7 69 13 P00 11 20 1 20 23 282 83 08 7 66 13 182 90 18 7 69 21	182 90 09 7 69 21 282 83 07 7 69 13 IAT 01 20 2 01 5 182 83 93 7 69 13 P00 11 20 1 20 23 282 83 08 7 66 13 182 90 18 7 69 21

	Variant 82	Variant 83	Variant 84	Variant 85	Variant 86
Variant name:	SAF INTRA IO 04-350	SAF MODUL US 3504	SAF MODUL US 3004	SAF MODUL OS 3504	SAF MODUL OS 3001
Number of Axles	4	4	4	4	1
Overslung/Underslung	O/SLUNG	U/SLUNG	U/SLUNG	O/Slung	O/Slung
Maximum Axle spread (m)	4.900	4.900	4.900	4.900	0
Dampers Part Numbers	2 376 0085 00 2 376 0086 00 2 376 0089 00	2 376 0027 00 2 376 0031 00 2 376 5032 00 2 376 0032 00	2 376 0027 00 2 376 0031 00 2 376 0032 00	2 376 5026 00 2 376 0032 00 2 376 0031 00 2 376 0026 00	2 376 5026 00 2 376 0031 00 2 376 0026 00 2 376 0032 00
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	350	350	300	350	300
Reference Drawings No of Suspension (parts list & assembly details)	182 90 09 7 69 21 282 83 07 7 69 13 IAT 01 20 2 01 5 182 83 93 7 69 13 P00 11 20 1 20 23 282 83 08 7 66 13 182 90 18 7 69 21	283 90 04 2 69 0 P00221092023 683836776910	183 90 94 2 69 0 P000150507 P00129082023 683836776910 C18312046690 C18312016690	C183 12 03 6 69 0-350, C183 12 02 6 69 0-350, C183 12 05 6 69 0-350 189 83 35 7 69 10 P00415062023 189 83 13 7 69 10 183 83 52 7 66 0 189 83 16 7 69 10 P00114072023	C183 12 02 6 69 0, C183 12 03 6 69 0, C183 12 05 6 69 0 P00127092022 283 90 05 2 69 0 P00114072023 683837576910 68383776910 183 90 97 2 69 0 683837676910 P30000074401

	Variant 87	Variant 88	Variant 89	Variant 90	Variant 91
Variant name:	SAF MODUL OS 3004	SAF MODUL OS 3501-Vertical Damper	SAF MODUL OS 3502-Vertical Damper	SAF MODUL OS 3503-Vertical Damper	SAF MODUL OS 3504-Vertical Damper
Number of Axles	4	1	2	3	4
Overslung/Underslung	O/Slung	O/SLUNG	O/SLUNG	O/SLUNG	O/SLUNG
Maximum Axle spread (m)	4.900	0.0	2.000	3.200	4.900
Dampers Part Numbers	2 376 5026 00 2 376 0031 00 2 376 0026 00 2 376 0032 00	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	300	350	350	350	350

	Variant 87	Variant 88	Variant 89	Variant 90	Variant 91
Reference Drawings No of Suspension (parts list & assembly details)	C183 12 02 6 69 0, C183 12 03 6 69 0, C183 12 05 6 69 0 P00127092022 283 90 05 2 69 0 P00114072023 683837576910 683837776910 183 90 97 2 69 0 683837676910 P30000074401	189833576910	189833576910	189833576910	189833576910

	Variant 92	Variant 93	Variant 94	Variant 95	Variant 96
Variant name:	SAF MODUL OS 3001-Vertical Damper	SAF MODUL OS 3002-Vertical Damper	SAF MODUL OS 3003-Vertical Damper	SAF MODUL OS 3004-Vertical Damper	SAF MODUL US 3501-Vertical Damper
Number of Axles	1	2	3	4	1
Overslung/Underslung	O/SLUNG	O/SLUNG	O/SLUNG	O/SLUNG	U/SLUNG
Maximum Axle spread (m)	0.0	2.000	3.200	4.900	0.0
Dampers Part Numbers	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	300	300	300	300	350
Reference Drawings No of Suspension (parts list & assembly details)	189833576910	189833576910	189833576910	189833576910	683836776910

	Variant 97	Variant 98	Variant 99	Variant 100	Variant 101
Variant name:	SAF MODUL US 3502- Vertical Damper	SAF MODUL US 3503-Vertical Damper	SAF MODUL US 3504-Vertical Damper	SAF MODUL US 3001-Vertical Damper	SAF MODUL US 3002-Vertical Damper
Number of Axles	2	3	4	1	2
Overslung/Underslung	U/SLUNG	U/SLUNG	U/SLUNG	U/SLUNG	U/SLUNG
Maximum Axle spread (m)	2.000	3.200	4.900	0.0	2.000
Dampers Part Numbers	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532	2 376 5032A 90045532
Smallest Tyre Size Designation	8.25R15	8.25R15	8.25R15	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825	825	825	825
Airbag Diameter (mm)	350	350	350	300	300
Reference Drawings No of Suspension (parts list & assembly details)					

	Variant 102	Variant 103
Variant name:	SAF MODUL US 3003-Vertical Damper	SAF MODUL US 3004-Vertical Damper
Number of Axles	3	4
Overslung/Underslung	U/SLUNG	U/SLUNG
Maximum Axle spread (m)	3.200	4.900
Dampers Part Numbers	2 376 5032A 90045532	2 376 5032A 90045532
Smallest Tyre Size Designation	8.25R15	8.25R15
Highest tyre pressure (Kpa)	825	825
Airbag Diameter (mm)	300	300
Reference Drawings No of Suspension (parts list & assembly details)	683836776910	683836776910

.....

Umesh Shamdasani

Director of Technical Assessment and Approvals team
Vehicle Safety Operations Branch

February 2025